

GENERAL SPECIFICATIONS

Bore Diameter:	12.5 mm (0.5")
Total Length:	31 cm (12")
Total Weight:	2.0 kg (4.4 lbs)
Height on Stand:	183 cm (72") Maximum
Composition:	Stainless Steel and Aluminium
Ignition Voltage:	24 volts; 1 amp
Laser System:	12.5 mm Single Laser Pointer
Liquid Projectile:	25 ml (0.85 oz.)
Liquid Load:	25 ml (1.7 oz.)
Peak Liquid Projectile Velocity:	500 m/s (1,3640 ft/s)
Kinetic Energy:	1.1 kJ
Recoil Impulse:	10 N-s
Vertical Adjustment:	180°
Horizontal Adjustment:	360°, for multi-purpose positioning
Barrel Composition:	Stainless Steel
Barrel Length:	25 cm (10")
Barrel Weight:	0.7 kg (1.5 lbs.)



12.5 mm Neutrex Disrupter on Tripod

DESCRIPTION

The 12.5mm Neutrex Disrupter is designed to disrupt small devices and packages. Its precision and accuracy are enhanced when paired with an X-ray, allowing for disruption of larger packages with a surgical shot. This disrupter is perfect for CBRNE devices where containment is crucial. Its lightweight design and ease of use make it easy to deploy on small robotic platforms, providing greater flexibility and reducing operator risk. The recommended maximum standoff is 1 meter (3 ft.), depending on the target.

Experience the proven performance and reliability of the 12.5mm Neutrex Disrupter for your precise disruption needs.

AMMUNITION

- A - Electrically Primed Cartridge (Low or Medium Velocity)
- B - 12.5 mm Avon Frangible (De-Armer)
- C - 12.5 mm Flathead Steel Slug (De-Armer)
- D - 12.5 mm Enhanced Chisel Head Steel Slug (De-Armer)
- E - Gel Shot



Ammunition is not included as part of the system. Warranty valid only with the use of Proparms ammunition.

ACCESSORIES



P2 Blasting Machine



Wire Wheel



Bore Sight Laser



12.5mm Single Laser Pointer



Knapsack

2133 Calypso St., Limoges ON, Canada K0A 2M0
+1 (450) 658-5207
info@proparms.com
proparms.com

PROP ARMS Ltd.

